

CD CONTROL PANEL

Description

- User friendly control panel for choice of airflow and supply air temperature.
- Symbol and text in the LCD-display indicate chosen settings.
- Optional connection via modular plugs or terminal block.
- The unit can be operated from several control panels.
- Commissioning of supply and extract airflow on each step.
- Timer function.
- Alarm indicates possible malfunction and time for filter change.



Control panel for the VR DC, -DCV and -DCV/B models.

The DCV and DCV/B units for wall installation are supplied with integrated control panel. Separate control panel, type CD, is used for control of DC-models and also for remote operation of the DCV and DCV/B-models.

Airflow and supply air temperature is set from one or more control panel(s). Symbol and text in the display indicate chosen settings; re-heater on, summer operation and time for filter change. Commissioning of airflow on supply and extract on each step is set from the CD panel. Timer function, for automatic change between day and night operation (installations in commercial buildings) is integrated. Alarms will indicate possible malfunctions and ensure safe and energy efficient operation.

The CD panel also has a user level for authorized installers and service personnel (password level).

The CD panel is connected to the unit by means of cable with quick connectors alternatively via 4-pole terminal block. Adaptor plugs to be used for fitting of more than one control panel.

Paragon Systems (Scotland) Ltd

The Office, Corbie Cottage, Maryculter, Aberdeen, AB12 5FT

Tel (+44)01224 735536 Fax (+44)01224 735537 e-mail: info@paragon-systems.co.uk